

AMENDMENT OF SOLICITATION/MODIFICATION OF CONTRACT				1. CONTRACT ID CODE		PAGE OF PAGES 1 2	
2. AMENDMENT/MODIFICATION NO. 0001		3. EFFECTIVE DATE 08/14/02		4. REQUISITION/PURCHASE REQ. NO.		5. PROJECT NO. (If applicable)	
6. ISSUED BY U.S. Army Engineer District, Wilmington 69 Darlington Avenue (28403) Post Office Box 1890 (28402-1890) Wilmington, North Carolina		CODE		7. ADMINISTERED BY (If other than Item 6) CODE			
8. NAME AND ADDRESS OF CONTRACTOR (No., street, county, State and ZIP Code)				(X)		9A. AMENDMENT OF SOLICITATION NO. DACW54-02-B-0008	
						9B. DATED (SEE ITEM 11) 07/18/02	
						10A. MODIFICATION OF CONTRACT/ORDER NO.	
						10B. DATED (SEE ITEM 11)	
CODE		FACILITY CODE					

11. THIS ITEM ONLY APPLIES TO AMENDMENTS OF SOLICITATIONS

☒ The above numbered solicitation is amended as set forth in Item 14. The hour and date specified for receipt of Offers ☐ is extended, ☒ is not extended. Offers must acknowledge receipt of this amendment prior to the hour and date specified in the solicitation or as amended, by one of the following methods:

(a) By completing items 8 and 15, and returning 2 copies of the amendment; (b) By acknowledging receipt of this amendment on each copy of the offer submitted; or (c) By separate letter or telegram which includes a reference to the solicitation and amendment numbers. FAILURE OF YOUR ACKNOWLEDGMENT TO BE RECEIVED AT THE PLACE DESIGNATED FOR THE RECEIPT OF OFFERS PRIOR TO THE HOUR AND DATE SPECIFIED MAY RESULT IN REJECTION OF YOUR OFFER. If by virtue of this amendment your desire to change an offer already submitted, such change may be made by telegram or letter, provided each telegram or letter makes reference to the solicitation and this amendment, and is received prior to the opening hour and date specified.

12. ACCOUNTING AND APPROPRIATION DATA (If required)

**13. THIS ITEM ONLY APPLIES TO MODIFICATION OF CONTRACTS/ORDERS.
IT MODIFIES THE CONTRACT/ORDER NO. AS DESCRIBED IN ITEM 14.**

CHECK ONE	A. THIS CHANGE ORDER IS ISSUED PURSUANT TO: (Specify authority) THE CHANGES SET FORTH IN ITEM 14 ARE MADE IN THE CONTRACT ORDER NO. IN ITEM 10A.
	B. THE ABOVE NUMBERED CONTRACT/ORDER IS MODIFIED TO REFLECT THE ADMINISTRATIVE CHANGES (such as changes in paying office, appropriation date, etc.) SET FORTH IN ITEM 14, PURSUANT TO THE AUTHORITY OF FAR 43.103(b).
	C. THIS SUPPLEMENTAL AGREEMENT IS ENTERED INTO PURSUANT TO AUTHORITY OF:
	D. OTHER (Specify type of modification and authority)

E. IMPORTANT: Contractor ☐ is not, ☐ is required to sign this document and return _____ copies to the issuing office.

14. DESCRIPTION OF AMENDMENT/MODIFICATION (Organized by UCF section headings, including solicitation/contract subject matter where feasible.)
IFB NO. DACW54-02-B-0008...Joint and Hatch Repairs, John H. Kerr Dam and Reservoir, Boydton, Virginia is amended as follows:

a. SECTION 07133: Delete existing Page 3 and Page 4 in their entirety and substitute enclosed revised pages.

Except as provided herein, all terms and conditions of the document referenced in Item 9A or 10A, as heretofore changed, remains unchanged and in full force and effect.

15A. NAME AND TITLE OF SIGNER (Type or print)		16A. NAME AND TITLE OF CONTRACTING OFFICER (Type or print)	
15B. CONTRACTOR/OFFEROR (Signature of person authorized to sign)		16B. UNITED STATES OF AMERICA (Signature of Contracting Officer)	
15C. DATE SIGNED		16C. DATE SIGNED	

14. DESCRIPTION OF AMENDMENT -- Cont'd

NOTE:

Text that is added or revised by this amendment is replaced in its entirety and/or underlined and printed in bold and/or stamped appropriately.

The text changes may have necessitated reformatting of subsequent text or pages. If this is the case, those pages have also been issued as amended pages but are not underlined with bold text.

Encls
As stated

and brand name. Materials shall be protected from freezing, moisture damage and moisture absorption in a weathertight enclosure, or shall be stored off the ground on pallets, and covered on top and all sides with breathable-type canvas tarpaulins. Damaged or deteriorated materials shall be removed from project site.

PART 2 PRODUCTS

2.1 DECK SEALANT

Deck sealant shall be CHEM-TRETE BSM as manufactured by Dynamit Nobel of America, Inc., 10 Link Drive, Rockleigh, New Jersey 07647, Telephone: (201) 767-1660, or approved equal. It shall be water miscible, colorless liquid conforming to the following:

2.1.1 Water Absorption

Water absorption for treated concrete shall not exceed 1% after a 48 hour submersion in water. A like sample of untreated concrete shall absorb around 4.8% under the same test in accordance with ASTM C 642. The above treated sample shall retain no more than 1.3% moisture after submerging in boiling water for 24 hours using the same test procedures.

2.1.2 Vapor Permeability

The treatment shall allow treated substrates to retain vapor permeability and application must be compatible with damp substrate surfaces. Verification of this property shall be demonstrated by treating sample specimen which is in a water saturated condition at the time of application, dryin the treated sample to a constant weight, and then performing ASTM C 642 testing procedure with the treated sample gaining no more than 1% of its weight when submerged for 24 hours.

2.1.3 Treated Surfaces

Treated surfaces shall display no staining, darkening, or texture changes.

PART 3 EXECUTION

3.1 SURFACE PREPARATION

Surfaces scheduled to receive the deck sealant shall be prepared in accordance with the sealant manufacturer's recommendations. Surface preparation shall be approved prior to application.

3.1.1 Treatment Area

The entire length of the road surface (curb to curb 23'-3"), from monolith 1 (Sta 201+64.67) through monolith 53 (Sta 229+50) is to receive deck sealant treatment.

3.1.2 Deck Repairs

Insure that all deck repairs have been made as shown on the drawings or as

otherwise directed.

3.1.3 Clean Surfaces

Surfaces shall be properly cleaned of dust, oil, and other materials with high pressure water, sandblasting, or other approved methods.

3.1.4 Test Section

Prior to treating the entire surface, an area no smaller than 10 foot by 10 foot shall be treated as specified in paragraph 3. After five days the area shall then be flooded with water in the presence of the Contracting Officer to demonstrate the sealant's effectiveness.

3.2 Qualification

The Contractor shall submit evidence that the applicator has been qualified by the sealant manufacturer, prior to commencing deck sealant application.

3.3 Method

The Contractor shall apply the sealant with a low pressure (15 psi maximum), airless, fan spray, coarse nozzle in accordance with the manufacturer's written recommendations. Scuppers shall be blocked as needed to restrict runoff during application. Scupper shall not be blocked during nonwork periods.

3.4 Coverage Rate

The rate of coverage shall be as recommended by the manufacturer for bridge decks, but shall be no more than 150 square feet per gallon.

3.5 Warranty

The waterproofing sealant installation shall be warranted by the manufacturers for a period of 10 years.

3.6 Traffic Control

One lane of traffic shall be maintained during application as described under Section 01570 "TRAFFIC REGULATION". Traffic shall not be allowed on the treated deck until the deck appears to be dry when compared to the untreated areas.

3.7 Measurement and Payment

There will be no measurement for payment of any work covered in this section. Payment for work called for under this specification section shall be made based on the lump sum amount listed item in the Bidding Schedule.

-- End of Section --